ThinkVision S22e-19 61C9KAT1EU

Product

ThinkVision S22e-19

Machine Type

61C9

Region

EMEA

Display Size

21.5"

View Area

476.06x267.79 mm

Panel

Vertical Alignment

Aspect Ratio

16:9

Resolution

1920x1080

Pixel Pitch

0.248x0.248 mm

Dot / Pixel Per Inch

102 dpi

View Angle (H / V)

178 / 178

Pixel Response Time

4 ms (Extreme mode) / 6 ms (normal mode)

Refresh Rate

60 Hz

Brightness

250 nits

Contrast Ratio

3000:1

Color Gamut

72% NTSC

Anti-glare Yes

Multiple Input

HDMI, VGA

USB Port

None

Camera None

Microphone

None

Speaker

None

Power Consumption (Typical / Maximum)

18W / 22W

Power Adapter

Integrated

Stand

Tilt Stand

Color

Black

Side Bezel Width

2 mm

Dimensions with Stand (HxWxD)

373.8x489.3x200.0 mm

Weight (Including Stand)

6.06 lb / 2.75kg

Monitor Cable

HDMI

ENERGY STAR

Yes

TCO

TCO 7.0

EPEAT

Silver

Low Blue Light / Eye Comfort / Eyesafe Display

Eye Comfort

Base Warranty

3-year

Operating System Support

Support Windows 7, Windows 10

Sync Technology

AMD FreeSvnc

CPU / Platform / Tiny Support

None / None / None

Display Ram / Storage / Card Slot

None / None / None

Wireless / Ethernet / Bluetooth

None / None / None

Touch Screen / Digitizer Pen / Battery

None / None / None

EAN/UPC/JAN

0192651335027

Announce Date

2018-06-26

WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo

may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



https://psref.lenovo.com

Visit psref website for the latest version of Product specifications Reference.
© Lenovo, 2021. All rights reserved.



Think Vision S22e-19

DISPLAY

Panel Size

21.5-inch

Screen Dimensions (W x H) (mm)

476.06 mm × 267.79 mm

Panel Type

3-side NearEdgelss, VA

Backlight

WLED

Aspect Ratio

16:9

Resolution

1920 x 1080 mm

Pixel Pitch (H x V) (mm)

0.2480 × 0.2480 mm

Dot/Pixel Per Inch (DPI/PPI)

102

Viewing Angle (H x V)

178°/178°

Response Time (gray to gray)

4 ms (extreme mode) 6 ms (normal mode)

Contrast Ratio (typical)

3000.1

Dynamic Contrast Ratio (typical)

Color Gamut NTSC (CIE 1931)

72% NTSC

Color Support (typical)

16.7M

Refresh rate

60 Hz

Brightness (typical)

250 cd/m²

CONNECTIVITY

Video Input Signals

1x VGA 1x HDMI14

Audio Out

Yes (3.5 mm)

MULTI-MEDIA

Optional Soundbar Support

Yes

SPECIAL FEATURES

Anti-Glare

Yes

Thin Client Support (Tinv)

Yes (by VESA mount PN:4XF0N03161)

Sync Technology

FreeSync™

POWFR

Power Consumption (Typ./Max)

18W / 22W

MECHANICAL

Tilt Angle (front / back)

-5°/ 22°

VESA Mount

Yes (100 x 100 mm)

Kensington Lock Slot

Yes

Cable Management

Yes

Bezel Color

Raven Black

Bezel Width (side)

20 mm

Bezel Width (top / bottom)

2.0 mm / 21.2 mm

DIMENSIONS

Size Packed (D x H x W) (mm/inch)

120 x 350 x 582 mm / 4.7 x 13.7 x 22.9 inch

Size Unpacked w/stand (D x H x W) (mm/inch)

(Lowest Position)

200.0 x 373.8 x 489.3 mm / 7.87 x 14.71 x 19.26 inch

Size Unpacked w/stand (D x H x W) (mm/inch)

(Highest Position)

200.0 x 373.8 x 489.3 mm / 7.87 x 14.71 x 19.26 inch

Size Unpacked w/o stand (D x H x W) (mm/inch) (Head Only)

41.5 x 296.8 x 489.3 mm / 1.63 x 11.68 x 19.26 inch

Weight Packed (kg/lbs.)

4.07kg / 8.97 lbs.

Weight Unpacked (kg/lbs.)

2.75kg / 6.06 lbs.

Weight (Monitor Head Only) (kg/lbs.)

2.46kg / 5.42 lbs.

WHAT'S IN THE BOX

Monitor with stand 1x HDMI Cable

1x Power Cable

Quick setup guide

CERTIFICATIONS

ENERGY STAR Rating

80

CCC

Yes

TCO

TCO 7.0/TCO Edge 2.0

EPEAT

Silver

ULE

Gold

RoHS Yes

Windows Certification

Windows 7. Windows 10

China Energy Efficiency Standard

Tier 2

Ambient Operating Temperature

0°C to 40°C

Low Blue Light

Yes









enovo



















